

TSC

The Smarter Choice.



TE200 SERIES – Desktop Thermal Transfer Bar Code Printer

SUPERIOR, FAST, AFFORDABLE PERFORMANCE, FEATURING LEGENDARY TSC DURABILITY

KEY FEATURES

- 152.4 mm (6") per second print speed
- 300 meter (984') ribbon supply on a 25.4 mm (1") core (coated outside)
- 72 to 110 meter (361') ribbon supply on a 12.7 mm (0.5") core (coated outside)
- 127 mm (5") OD internal media supply, optional external media holder supports 214 mm (8.4") OD label rolls on 76.2 mm (3") core
- Print mechanism for kiosk applications
- 400 MHz 32-bit RISC processor with 16 MB SDRAM, 8 MB Flash memory for TE200/TE300, and 64 MB SDRAM, 128 MB Flash memory for TE210/TE310
- Internally scalable true type fonts
- TSPL-EZD firmware emulates TPLE, TPLZ, and TPLD languages out of the box
- Free Windows® drivers and label design software (available via download)
- ENERGY STAR® qualified

APPLICATIONS

- **Manufacturing & Warehousing**
 - Work in Progress
 - Item Labels
 - Instruction Labels
 - Agency Labels
- **Healthcare**
 - Patient Identification
 - Pharmacy
 - Specimen Identification
- **Parcel Post**
 - Shipping Labels
 - Receiving Labels
- **Small Office/Home Office**
 - Shipping Labels
 - File folder labels
 - Product identification
- **Retail Marking**
 - Price Tags
 - Shelf Labels
 - Jewelry Tags



TE200 SERIES – Desktop Thermal Transfer Bar Code Printer

PRINTER MODEL	TE200	TE300	TE210	TE310
Resolution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)
Printing method	Thermal Transfer & Direct Thermal			
Max. print speed	152.4 mm (6")/second	127 mm (5")/second	152.4 mm (6")/second	127 mm (5")/second
Max. print width	108 mm (4.25")	105.7 mm (4.16")	108 mm (4.25")	105.7 mm (4.16")
Max. print length	2,794 mm (110")	1,016 mm (40")	25,400 mm (1000")	11,430 mm (450")
Enclosure	ABS plastic			
Physical dimension	204 mm (W) x 164 mm (H) x 280 mm (D) 8.03" (W) x 6.46" (H) x 11.02" (D)			
Weight	2.4 kg (5.29 lbs)		2.5 kg (5.51 lbs)	
Label roll capacity	127 mm (5") OD			
Ribbon	300 m long, max. OD 67 mm, 1" core (ink coated outside) 110 m long, max. OD 40 mm, 0.5" core (ink coated outside)			
Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3")			
Processor	32-bit RISC CPU			
Memory	<ul style="list-style-type: none"> • 8 MB Flash memory • 16 MB SDRAM 		<ul style="list-style-type: none"> • 128 MB Flash memory • 64 MB SDRAM 	
Interface	<ul style="list-style-type: none"> • USB 2.0 • Internal Bluetooth 4.0 (factory option) 		<ul style="list-style-type: none"> • USB 2.0 • Internal Ethernet, 10/100 Mbps • RS232 • USB host, for scanner or PC keyboard • Internal Bluetooth 4.0 (factory option) • External Bluetooth (user option) • 802.11 a/b/g/n Wi-Fi (factory option) 	
Power	External universal switching power supply <ul style="list-style-type: none"> • Input: AC 100-240V, 2.5A, 50-60Hz • Output: DC 24V, 2.5A, 60W 			
Operation switch, button LED	1 power switch, 1 feed and pause button & 1 LED (3 colors: green, amber & red)			
Sensors	<ul style="list-style-type: none"> • Transmissive gap sensor • Black mark reflective sensor (position adjustable) • Ribbon end sensor • Head open sensor 			
Real Time Clock	N/A		Standard	
Buzzer	N/A		Standard	
Internal fonts	<ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font 			
Bar code	<ul style="list-style-type: none"> • 1D bar code Code 128UCC, Code 128 subsets A, B, C, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code 39, Code 39 with check digit, Code 93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, Code 11, TELEPEN, TELEPENN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS • 2D bar code GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417 			
Font and barcode rotation	0, 90, 180, 270 degree			
Printer language	TSPLEZD (Compatible to EPL, ZPL, ZPL II, DPL)			
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)			
Media width	20 ~ 112 mm (0.8" ~ 4.4")			
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)			
Media core diameter	25.4 ~ 38 mm (1" ~ 1.5")			
Label length	5 ~ 2,794 mm (0.2" ~ 110")	5 ~ 1,016 mm (0.2" ~ 40")	5 ~ 25,400 mm (0.2" ~ 1000")	5 ~ 11,430 mm (0.2" ~ 450")
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing			
Safety regulation	FCC Class A, CE Class A, C-Tick Class A, UL, cUL, TÜV/safety, CCC, EAC, CoC, BIS, KC, Energy Star®		FCC Class B, CE Class B, C-Tick Class B, UL, cUL, TÜV/safety, CCC, EAC, CoC, BIS, KC, Energy Star®	
Environmental concern	Comply with RoHS, REACH, WEEE			
Accessories	<ul style="list-style-type: none"> • Windows labeling software CD disk • Quick start guide • USB cable • Power cord • External universal switching power supply • 1" label spindle, fixing tab x 2, 1.5" adapter x 2 • 1" ribbon spindle x 2 for 300M ribbon • 1" ribbon paper core 			
Limited warranty	<ul style="list-style-type: none"> • Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first 			
Factory options	<ul style="list-style-type: none"> • Internal Bluetooth 4.0 		<ul style="list-style-type: none"> • 802.11 a/b/g/n Wi-Fi • Internal Bluetooth 4.0 	
Dealer options	N/A		<ul style="list-style-type: none"> • Peel-off module • Guillotine cutter (full cut and partial cut) 	
User options	<ul style="list-style-type: none"> • External roll mount, media OD. 214 mm (8.4") with 76.2 mm (3") core 		<ul style="list-style-type: none"> • External roll mount, media OD. 214 mm (8.4") with 76.2 mm (3") core • External Bluetooth module (serial interface) • KP-200 Plus keyboard display unit 	



CORPORATE HEADQUARTERS
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

LI ZE PLANT
TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6677
 E-mail: apac_sales@tscprinters.com

AMERICAS
TSC Auto ID Technology America Inc.
 Tel: +1 657 258 0808
 E-mail: americas_sales@tscprinters.com

MEXICO
TSC Mexico Representative Office
 Tel: +1 52 (33) 3673 1406
 E-mail: americas_sales@tscprinters.com

BRAZIL
TSC Brazil Representative Office
 Tel: +55 (11) 3554 7225
 E-mail: americas_sales@tscprinters.com

EMEA
TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 000
 E-mail: emea_sales@tscprinters.com

RUSSIA
TSC Auto ID Technology EMEA GmbH
 Tel: +7 495 249 9017
 E-mail: emea_sales@tscprinters.com

MIDDLE EAST
TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: emea_sales@tscprinters.com

ASIA PACIFIC
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

INDIA
TSC India Distributor's Office
 Tel: +91 2267 082 465
 E-mail: apac_sales@tscprinters.com

CHINA
Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: apac_sales@tscprinters.com

KOREA
TSC Korea Representative Office
 Tel: +82 2 852 3322
 E-mail: apac_sales@tscprinters.com



TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
 © 2020 TSC Auto ID Technology Co., Ltd.
 Product models and Specifications are subject to change without notice.
 Contact your TSC sales representative for specific information.